

SDX stag

Lagerprodukt

		Stag med R-Gänga							
		R25N	R32L	R32N	R32S	R32X	R38N	R51L	R51N
SDX benämning		R25-200	R32-260	R32-280	R32-360	R32-405	R38-500	R51-550	R51-800
Ytter diameter	mm	25	32	32	32	32	38	51	51
Sträck last	kN	150	200	230	280	300	400	450	630
Brott last	kN	200	260	280	360	405	500	550	800
Inner diameter	mm	10	19	20	18.5	14	19	36	28
Area	mm ²	318	395	363	433	535	764	803	1121
Vikt	kg/m	2.5	3.1	2.9	3.4	4.2	6.0	6.3	8.8

Stag med T-Gänga

Se nästa Sida

		Mutter							
Ytter diameter	mm	25	32	32	32	32	38	51	51
Nyckelvid	mm	41	46	46	46	46	50	75	75
Längd	mm	35	45	45	65	65	60	70	70
Vikt	kg	0.3	0.4	0.4	0.6	0.6	0.5	1.5	1.5

		Skarvhylsa							
Inner diameter	mm	25	32	32	32	32	38	51	51
Ytter diameter	mm	36	42	42	42	42	52	63	63
Längd	mm	150	145	160	190	190	220	140	200
Vikt	kg	0.6	0.7	0.8	1.0	1.0	1.8	1.3	1.9

		Platta							
Inner diameter	mm	25	32	32	32	32	38	51	51
Bredd	mm	150	200	200	200	200	200	200	250
Tjocklek	mm	8	10	10	12	12	12	30	40
Innerhål	mm	30	35	35	35	35	41	60	60
Vikt	kg	1.4	3.0	3.0	3.3	3.3	3.6	8.8	18.5

SDX stag

Lagerprodukt		Stag med T-Gänga													
		T30/16	T30/14	T30/11	T40/20	T40/16	T52/26	T73/56	T73/53	T73/45	T73/35	T76N	T76S	T103/78	T103/51
SDX benämning		T30-220	T30-260	T30-320	T40-540	T40-660	T52-929	T73-1035	T73-1160	T73-1575	T73-1865	T76N-1600	T76N-1900	T103-2280	T103-3460
Ytter diameter	mm	30	30	30	40	40	52	73	73	73	73	76	76	103	103
Sträck last	kN	180	220	260	430	525	730	830	970	1270	1430	1200	1500	1800	2730
Brott last	kN	220	260	320	540	660	929	1035	1160	1575	1865	1600	1900	2280	3460
Inner diameter	mm	16	14	11	20	16	26	56	53	45	35	49	45	78	51
Area	mm ²	344	357	420	739	917	1261	1401	1682	2268	2701	2229	2675	3223	5682
Vikt	kg/m	2.7	2.8	3.3	5.8	7.2	9.9	11.0	13.2	17.8	21.2	17.5	21.0	25.3	44.6

		Mutter													
Ytter diameter	mm	30	30	30	40	40	52	73	73	73	73	76	76	103	103
Nyckelvid	mm	46	46	46	65	65	80	95	95	95	95	100	100	125	125
Längd	mm	35	35	35	50	50	70	70	70	70	70	80	80	80	80
Vikt	kg	0.4	0.4	0.4	0.9	0.9	2.4	2.2	2.2	2.2	2.2	2.7	2.7	3.4	3.4

		Skarvhylsa													
Inner diameter	mm	30	30	30	40	40	52	73	73	73	73	76	76	103	103
Ytter diameter	mm	38	38	38	54	57	70	89	89	95	95	95	97	123	132
Längd	mm	105	105	105	140	140	160	235	235	245	245	200	220	255	290
Vikt	kg	0.4	0.4	0.4	1.2	1.4	2.3	4.3	4.3	6.2	6.2	4.3	5.4	7.4	12.5

		Platta													
Inner diameter	mm	30	30	30	40	40	52	73	73	73	73	76	76	103	103
Bredd	mm	200	200	200	200	200	220	250	250	250	250	250	250	300	300
Tjocklek	mm	8	8	8	12	15	35	40	40	40	40	40	40	50	50
Innerhål	mm	36	36	36	54	54	65	80	80	80	80	80	80	110	110
Vikt	kg	2.5	2.5	2.5	3.5	4.6	12.1	8.0	8.0	8.0	8.0	19.1	19.1	32.6	32.6