

**BAT MkIII Filter Tips****BAT MkIII Std (#2-100)**General

The BAT MkIII Std Filter Tip has been designed as an all-round filter tip for installations, measurements and groundwater sampling in the saturated soil zone.

Filter tip body

Material: High-strength thermoplastic POM H

Filter

Material: Porous, polyteten plastic

Filter dimensions: Height: 35mm, diameter: 31,5mm

Coeff. of permeability: Approx.  $1 \times 10^{-5}$  m/s

Installation

Method of installation: Normally push-in installation in fine-grained soils.

Installation force: Max. 25 kN in fine-grained soils.

**BAT MkIII HD (#2-101)**General

The BAT MkIII HD Filter Tip, which has a replaceable filter, has been designed for installations, measurements and groundwater sampling in the saturated soil zone.

The body of stainless steel, allows extra installation force for "push-in" installations in fine-grained soils.

Filter tip body

Material: Acid proof steel

Filter

Material: Porous, polyteten plastic

Filter dimensions: Height: 20 mm, diameter: 31,5mm

Coeff. of permeability: Approx.  $1 \times 10^{-5}$  m/s

Installation

Method of installation: Normally push-in installation in fine-grained soils.

Installation force: Max. 100 kN in fine-grained soils.

**BAT MkIII Vadose (#2-102)**General

The BAT MkIII Vadose Filter Tip. This filter tip has a body of high-strength thermoplastic and a replaceable, fine-porous ceramic filter. The BAT MkIII Vadose functions as a tensiometer and is thus designed for installations and measurements in the unsaturated soil zone.

Filter tip body

Material: High-strength thermoplastic POM H

Filter

Material: Fine-porous ceramic

Filter dimensions: Height: 35 mm, diameter: 25,5 mm

"Bubbling pressure": Approx. 15 m H<sub>2</sub>O

Coeff. of permeability: Approx.  $1 \times 10^{-7}$  m/s

Installation

Method of installation: Normally, push-in installation in a pre-augered hole.